

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

1           1. (Currently amended) A method for enabling a database system to prove  
2   that an origin system sent a message, comprising:  
3           receiving the message and a signed first digest of the message at a  
4   database system from the origin system, wherein the signed first digest was  
5   created by signing a digest of the message using an origin private encryption key;  
6           using an origin public encryption key that is associated with the origin  
7   private encryption key to verify that the signed first digest was signed by the  
8   origin system, thereby proving that the origin system created and sent the  
9   message; and  
10           persistently storing the signed first digest with the message, thereby which  
11   ~~enabling~~ enables the database system to present the signed first digest as proof  
12   that the origin system sent the message, thereby preventing the sender from  
13   persuasively denying that the sender sent the message.

1           2. (Canceled).

1           3. (Previously presented) The method of claim 22, further comprising  
2   passing the message and the digest through a plurality of queues between the  
3   origin and the recipient, whereby the recipient and the origin are subscribers of  
4   different queues.

1           4. (Original) The method of claim 3, further comprising passing the  
2 message and the digest through a plurality of databases, wherein each database in  
3 the plurality of databases includes at least one queue of the plurality of queues.

1           5. (Previously presented) The method of claim 1, wherein the origin public  
2 encryption key and the origin private encryption key are a key pair of a public key  
3 encryption system.

1           6. (Previously presented) The method of claim 22, wherein the recipient  
2 public encryption key and the recipient private encryption key are a key pair of a  
3 public key encryption system.

1           7. (Previously presented) The method of claim 1, wherein computing the  
2 digest includes using one of message digest 2 (MD2), message digest 4 (MD4),  
3 message digest 5 (MD5), secure hash algorithm (SHA), and secure hash algorithm  
4 1 (SHA1).

1           8. (Currently amended) A computer-readable storage medium storing  
2 instructions that when executed by a computer cause the computer to perform a  
3 method for enabling a database system to prove that an origin system sent a  
4 message, the method comprising:  
5           receiving the message and a signed first digest of the message at a  
6 database system from the origin system, wherein the signed first digest was  
7 created by signing a digest of the message using an origin private encryption key;  
8           using an origin public encryption key that is associated with the origin  
9 private encryption key to verify that the signed first digest was signed by the  
10 origin system, thereby proving that the origin system created and sent the  
11 message; and

12            persistently storing the signed first digest with the message, ~~thereby which~~  
13    ~~enabling enables~~ the database system to present the signed first digest as proof  
14    that the origin system sent the message, thereby preventing the sender from  
15    persuasively denying that the sender sent the message.

1            9. (Canceled).

1            10. (Previously presented) The computer-readable storage medium of  
2    claim 23, the method further comprising passing the message and the digest  
3    through a plurality of queues between the origin and the recipient, whereby the  
4    recipient and the origin are subscribers of different queues.

1            11. (Original) The computer-readable storage medium of claim 10, the  
2    method further comprising passing the message and the digest through a plurality  
3    of databases, wherein each database in the plurality of databases includes at least  
4    one queue of the plurality of queues.

1            12. (Previously presented) The computer-readable storage medium of  
2    claim 8, wherein the origin public encryption key and the origin private encryption  
3    key are a key pair of a public key encryption system.

1            13. (Previously presented) The computer-readable storage medium of  
2    claim 23, wherein the recipient public encryption key and the recipient private  
3    encryption key are a key pair of a public key encryption system.

1            14. (Previously presented) The computer-readable storage medium of  
2    claim 8, wherein computing the digest includes using one of message digest 2

3 (MD2), message digest 4 (MD4), message digest 5 (MD5), secure hash algorithm  
4 (SHA), and secure hash algorithm 1 (SHA1).

1 15. (Currently amended) An apparatus for enabling a database system to  
2 prove that an origin system sent a message, comprising:  
3 a first receiving mechanism that is configured to receive the message and a  
4 signed first digest of the message at a database system from the origin system,  
5 wherein the signed first digest was created by signing a digest of the message  
6 using an origin private encryption key;  
7 a first verifying mechanism that is configured to use an origin public  
8 encryption key that is associated with the origin private encryption key to verify  
9 that the signed first digest was signed by the origin system, thereby proving that  
10 the origin system created and sent the message; and  
11 a first storing mechanism that is configured to persistently store the signed  
12 first digest with the message, ~~thereby which enabling enables~~ the database system  
13 to present the signed first digest as proof that the origin system sent the message,  
14 thereby preventing the sender from persuasively denying that the sender sent the  
15 message.

1 16. (Canceled).

1 17. (Previously presented) The apparatus of claim 24, further comprising a  
2 passing mechanism that is configured to pass the message and the digest through a  
3 plurality of queues between the origin and the recipient, whereby the recipient and  
4 the origin are subscribers of different queues.

1 18. (Original) The apparatus of claim 17, wherein the passing mechanism  
2 is further configured to pass the message and the digest through a plurality of

3 databases, wherein each database in the plurality of databases includes at least one  
4 queue of the plurality of queues.

1 19. (Previously presented) The apparatus of claim 15, wherein the origin  
2 public encryption key and the origin private encryption key are a key pair of a  
3 public key encryption system.

1 20. (Previously presented) The apparatus of claim 24, wherein the  
2 recipient public encryption key and the recipient private encryption key are a key  
3 pair of a public key encryption system.

1 21. (Previously presented) The apparatus of claim 15, wherein computing  
2 the digest includes using one of message digest 2 (MD2), message digest 4  
3 (MD4), message digest 5 (MD5), secure hash algorithm (SHA), and secure hash  
4 algorithm 1 (SHA1).

1 22. (Previously presented) The method of claim 1, further comprising:  
2 receiving a signed receive-request from a recipient system for receiving  
3 the message, wherein the receive-request is signed using a recipient private  
4 encryption key;  
5 validating the signed receive-request using a recipient public encryption  
6 key that is associated with the recipient private encryption key;  
7 sending a second digest of the message to the recipient system;  
8 receiving a signed second digest from the recipient system, wherein the  
9 signed second digest was created by signing the second digest using the recipient  
10 private encryption key;

11           validating the signed second digest using the recipient public encryption  
12   key, thereby proving that the recipient system requested to receive the message;  
13   and  
14           persistently storing the signed second digest, thereby enabling the database  
15   system to present the signed second digest as proof that the recipient system  
16   requested to receive the message.

1           23. (Previously presented) The computer-readable storage medium of  
2   claim 8, the method further comprising:  
3           receiving a signed receive-request from a recipient system for receiving  
4   the message, wherein the receive-request is signed using a recipient private  
5   encryption key;  
6           validating the signed receive-request using a recipient public encryption  
7   key that is associated with the recipient private encryption key;  
8           sending a second digest of the message to the recipient system;  
9           receiving a signed second digest from the recipient system, wherein the  
10   signed second digest was created by signing the second digest using the recipient  
11   private encryption key;  
12           validating the signed second digest using the recipient public encryption  
13   key, thereby proving that the recipient system requested to receive the message;  
14   and  
15           persistently storing the signed second digest, thereby enabling the database  
16   system to present the signed second digest as proof that the recipient system  
17   requested to receive the message.

1           24. (Previously presented) The apparatus of claim 15, further comprising:

2           a second receiving mechanism configured to receive a signed  
3 receive-request from a recipient system for receiving the message, wherein the  
4 receive-request is signed using a recipient private encryption key;  
5           a second validating mechanism configured to validate the signed  
6 receive-request using a recipient public encryption key that is associated with the  
7 recipient private encryption key;  
8           a second sending mechanism configured to send a second digest of the  
9 message to the recipient system;  
10          a third receiving mechanism configured to receive a signed second digest  
11 from the recipient system, wherein the signed second digest was created by  
12 signing the second digest using the recipient private encryption key;  
13          a third validating mechanism configured to validate the signed second  
14 digest using the recipient public encryption key, thereby proving that the recipient  
15 system requested to receive the message; and  
16          a second storing mechanism configured to persistently store the signed  
17 second digest, thereby enabling the database system to present the signed second  
18 digest as proof that the recipient system requested to receive the message.